

NUTEC 600



NUTEC 800

Kennemerweg 4
3641 SK Mijdrecht (Holland)

P.O.Box 1
3640 AA Mijdrecht (Holland)
phone +31 (0)297 - 293.200
telefax +31 (0)297 - 285.930

product information

PERFORMANCE AND RATINGS, based on Groningen gas

NUTEC	NUTEC 600	NUTEC 800
PERKINS, engine type	4012 TESI	4016 TESI
Electrical output (kW)	610	810
Thermical output (kW)	849	1141
Gas consumption (Nm ³ /h)	185,4	248
Standard max. return temperature (°C)	80	80
Max. intercooler temperature (°C)	75	75
STAMFORD generator rating (kVA)	910	1110

MEASUREMENTS AND WEIGHT

NUTEC	NUTEC 600	NUTEC 800
Measurement (mm) l x w x h	6500 x 3500 x 2500	6900 x 3700 x 2500
Weight (kg) incl. canopy	13.000	15.500

ENVIRONMENT

NO_x emission : < 140 gram/GJ x η_{ind} /30
Oil consumption : < 0,2 gram/kWh

SOUNDPRESSURE

Canopy : 75 or 65 dB(A) at 1 meter
Exhaust stack : according environment law

January 2000

Nedalo, supplier of Combined Heat and Power units, Marine and Industrial engines, Standby power units, Maintenance and Service

Nedalo, leverancier van Warmte/Kracht installaties, Scheeps- en Industriebmotoren, Noodstroomaggregaten, Onderhoud en Service



NEDALO BV

